MIDLAND COUNTY ROAD COMMISSION

SPECIAL PROVISION FOR

HOT MIX ASPHALT CRACK TREATMENT

MCRC:ALB 08-03-17

a. Description. The work consists of treating cracks in Hot Mix Asphalt (HMA) surfaces in accordance with section 502 of the 2012 MDOT Standard Specifications For Construction with the following exceptions:

- 1. All cracks shall be treated as working cracks with the Saw or Rout and Seal process.
- **b. Materials.** Provide materials in accordance with subsection 502.02.A of the Standard Specifications for Construction.
- **c. Construction.** All construction must be in accordance with subsection 502.03 of the Standard Specifications for Construction with the following modification:
 - 1. Delete section 502.03.D.2 Overband
- **d. Maintaining Traffic.** Maintain traffic according to the MDOT Maintaining Traffic Typicals and the Standard Specifications for Construction. No work shall be performed or lane closures allowed during the Labor Day holiday period, as defined from noon Thursday until normal starting time on Tuesday.
- e. Measurement and Payment.

Pay Item	Pay Unit
HMA Crack Treatment, Roadbed	Roadbed Mile

HMA Crack Treatment. The Engineer will measure HMA Crack Treatment, Roadbed along the roadway centerline. This measurement includes traffic lanes, paved shoulders, auxiliary lanes, and ramps to the 2-foot gore point. For divided highways, the Engineer will measure the roadway separately in each direction.

The unit price for HMA Crack Treatment, Roadbed includes the cost of all materials, equipment, and traffic control devices necessary to prepare and treat all cracks with the saw or rout and seal process.